



## MAGIC-L

**Build Volume:** 310×310×480 mm

**Printing Temperature:** Up to 275°C

**Hot Bed Temperature:** Up to 110°C

**Extrusion System:** Dual Extruder

**Majority of the Materials on Market:** PLA, CF-PLA, ABS, TPU, PETG, PA, CF-PA, PC, CF-PC, PP...

## Specification

Principle: Fused Filament Fabrication (FFF)

File Type: STL, OBJ, 3MF, GCODE

Filament Diameter: 1.75 mm

Data Transmission: SD Card, Wi-Fi

Layer Thickness: 0.05 - 0.3 mm

Machine Size: 508×623×777 mm

Position Resolution: X/Y: 12.5 μm Z: 1.25 μm

Net Weight: 48KG

Supplied Software: IEMAI 3D EXPERT

Gross Weight: 68KG

Other Software: Cura, Simplify3D

Power: 200V-250V 50~60Hz 750W

## Features

Power Failure Recovery

Wi-Fi Control

Filament Absent Warning

Individual Motion Dual Extruder

Auto-Shut Down System

MAGIC-L is specially designed for large scale and massive print, with a temperature of 275°C extruder temperature and 110°C hot bed temperature, it can support most of the plastic on the market. It had a modular mechanism on the extruder which allow it to have simple maintenance.

### About IEMAI 3D

IEMAI 3D is a global industrial-grade 3D printer brand, dedicated to providing users with powerful 3D printers and high-performance materials.

### Contact:

+86-0769-83060912  
info@iemai3d.com  
NO.10 Jiling industrial road,  
Lianping, Dalingshan Town,  
Dongguan, Guangdong, China