



YM-AUTO-600

Build Volume: 600×600×100 mm

Printing Temperature: Up to 275°C

Hot Bed Temperature: Up to 80°C

Extrusion System: Two In One Extruder

Function: UV Light Curing + Manual Gluing

Material Supported: Specialized Filament For Advertising

Letter, Light Pass And Non Light Pass Filaments

Item	YM-AUTO-600
Printing Size (L × B × H)	600×600×100 mm
Machine Size (L × B × H)	965×1100×800 mm
Packing Size (L × B × H)	1015×1150×965 mm
Net Weight	160KG
Gross Weight	180KG
Power	100~250 V, 50~60 Hz 2800W

About IEMAI 3D

IEMAI 3D is a global industrial-grade 3D printer brand, dedicated to providing users with powerful 3D printers and high-performance materials.

Contact:

+86-0769-83060912

info@iemai3d.com

NO.10 Jiling industrial road,
Lianping, Dalingshan Town,
Dongguan, Guangdong, China

Common	<p>Principle: Fused Filament Fabrication</p> <p>Extrusion System: Two In One Extruder</p> <p>Filament Diameter: 1.75 mm</p> <p>Position Resolution: X/Y: 8.9 μm Z: 2.5 μm</p> <p>Printing Speed: 0 - 150 mm/s</p> <p>Printing Platform: Glass Plate</p> <p>Print Bed Temperature: 80°C</p> <p>Heated Bed Materials: Silicon</p> <p>Printing Platform Auto Calibration: Support</p> <p>Power Failure Recovery: Support</p> <p>Supporting Materials: Specialized Filament For Advertising Letter, Light Pass And Non Light Pass Filaments</p> <p>Layer Thickness: 0.2 – 0.4 mm</p> <p>Nozzle Diameter: 0.6 mm (Default), 0.4 mm, 0.8 mm, 1.0 mm (Choosable)</p> <p>Extruder Temperature: 275 °C</p> <p>Connection Control: Wi-Fi, LAN, SD Card</p> <p>Suggest Operating Environment: 15-30°C, relatively humidity 10-90%, No Moisture Condensation</p> <p>Storage Temperature: -25 - 55 °C, relatively humidity 10-90%, No Moisture Condensation</p> <p>Technology Certification: CE, RoHS</p> <p>Air Filter: Activated Carbon Filters (Choosable)</p>	
Software	<p>Supplied Software: IEMAI 3D ADV (2D to 3D)</p> <p>Operating System: Windows 64 Bit</p> <p>File Type: STL, OBJ, 3MF</p> <p>Output: GCODE</p>	
Features	<p>Power Failure Recovery</p> <p>Filament Absent Warning</p> <p>Auto-Shut Down System</p> <p>Manual Acrylic Gluing Function</p> <p>Auto Leveling</p> <p>Bottom Plate Printing</p> <p>UV Light Curing System</p> <p>UV Light At Base And Top</p>	