



## YM-NT-750

**Build Volume : 750×750×750 mm**

**Printing Temperature : Up to 275°C**

**Hot Bed Temperature: : Up to 120°C**

**Extrusion System : Dual Extruder For 1.75 mm Filament Or Single Extruder For 2.85/3.0mm Filament**

**Majority of the Materials on Market : ASA, ABS, CF-ABS, PETG, HIPS, PC, PA, TPU, PLA, CF-PLA, PVA...**

Item	YM-NT-750
Printing Size (L × B × H)	750×750×750 mm
Machine Size (L × B × H)	1642×1110×1320 mm
Packing Size (L × B × H)	1800×1300×1550 mm
Net Weight	400KG
Gross Weight	450KG
Power	200V-250V 50~60Hz 4500W

<p>Common</p>	<p>Principle: Extrusion System: Filament Diameter: Position Resolution: Printing Speed: Printing Platform: Print Bed Temperature: Heated Bed Materials: Printing Platform Auto Calibration: Power Failure Recovery: Supporting Materials: Layer Thickness: Nozzle Diameter: Extruder Temperature: Connection Control: Suggest Operating Environment: Storage Temperature: Technology Certification: Air Filter:</p>	<p>Fused Filament Fabrication Dual Extruder For 1.75 mm Filament Or Single Extruder For 2.85/3.0mm (Choosable) 1.75 mm , 2.85/3.0mm (Choosable) X/Y: 5.86 μm Z: 1.56 μm 0 - 150 mm/s Glass Plate, Fixed 120°C Silicon Support Support ASA, ABS, CF-ABS, PETG, HIPS, PC, PA, TPU, PLA, CF-PLA, PVA... 0.1 – 0.6 mm 0.8 mm (Default), 0.4 mm, 0.6 mm, 1.0 mm 2.0 mm (Choosable) 275 °C Wi-Fi, LAN, SD Card 15-30°C, relatively humidity 10-90%, No Moisture Condensation -25 - 55 °C, relatively humidity 10-90%, No Moisture Condensation CE, RoHS Activated Carbon Filters (Choosable)</p>
<p>Software</p>	<p>Supplied Software: Operating System: File Type: Output:</p>	<p>IEMAI 3D EXPERT, Cura, Simplify3D Windows 64 Bit STL, OBJ, 3MF GCODE</p>
<p>Features</p>	<p>Power Failure Recovery Filament Absent Warning Auto-Shut Down System WIFI Control Dual Or Single Extruder Modularization Camera Monitoring (Choosable)</p>	